



Provisional Technical Data Sheet

Product Type

Linear Low Density Polyethylene

Product Name

SCGC™ LLDPE

Product Grade

L1211FA

Product Description

SCGC™ L1211FA is a butene LLDPE resin. It is recommended for general purpose bag with high productivity and can be blended with HDPE and LDPE to improve seal and tear strength.

Typical Application

- General purpose bag
- Industrial bag
- Rice bag

Product Characteristics

- High productivity
- Barefoot (nonslip/anti-blocking agent)
- Good optical properties
- Food contact applicable

International Compliance

- Under evaluation

Physical Properties

Properties	Test Method	Typical Value	Unit
Melt Flow Rate	ASTM D 1238 @ 190 °C, 2.16 kg	1.0	g/ 10 min
Density	ASTM D 1505	0.918	g/cm ³
Melting Point	ASTM D 2117	120	°C
Viscat Softening Point	ASTM D 1525	102	°C
Brittleness Temperature	ASTM D 746	< -70	°C
Film Properties			
Tensile Strength at Yield	ASTM D 882	MD : 120*, TD: 125*	kg/cm ²
Tensile Strength at Break	ASTM D 882	MD : 360*, TD: 260*	kg/cm ²
Tensile Modulus, 2% Secant	ASTM D 882	MD : 1640*, TD: 1860*	kg/cm ²
Elongation at Break	ASTM D 882	MD : 650*, TD: 770*	%
Elmendorf Tear Strength	ASTM D 1922	MD : 210*, TD : 330*	g
Dart Impact Strength	ASTM D 1709	130*	g
Haze	ASTM D 1003	10*	%
Gloss	ASTM D 2457	65*	%

Note:

- The given values are typical values measured on the product. Values herein are not to be constructed as a product specification.
- Conversion factor for changing unit from kg/cm² to MPa is divided by 10.20.
- (*) Properties obtained from experiments on a pilot line, Film thickness 25 microns, BUR 2.5:1, MD = Machine Direction, TD = Transverse Direction.



Provisional Technical Data Sheet

Product Type

Linear Low Density Polyethylene

Product Name

SCGC™ LLDPE

Product Grade

L1211FA

Processing Guidelines

The actual extrusion condition depends on type of using machine, size and film thickness of product required. Generally, Melt temperature should be 180-200°C with Blow up ratio (BUR) 2-3 times of die diameter.

Product Technical Assistance

For technical assistance or further information on this product, please contact Long Son Petrochemicals technical services or SCG Chemicals technical services at the address or telephone number as specified below.

Product Available Form

- Pellet

Product Packaging

- 25 kg loose bag
- 25 kg stretch wrap palletized
- 750 kg big bag

Storage

- Store in original container in tidy according to the manual of Handling and Storage from SCG Chemicals Company Limited.
- Product(s) should be stored in dry and dust free location at temperature below 50 °C and protected from direct sunlight and/or heat, well-ventilated area, away from incompatible materials and food and drink, as this may lead to quality deterioration, which results in odor generation and color changes and can have negative effects on the physical properties of this product.
- Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.
- The storage area should be stable and not be slopped.

Safety

- The product is not classified as a hazardous material.
- Please see our Safety Data Sheet for details on various aspects of safety, recovery, and disposal of the products; for more information, contact your Long Son Petrochemicals technical services or SCG Chemicals technical services.



Provisional Technical Data Sheet

Product Type

Linear Low Density Polyethylene

Product Name

SCGC™ LLDPE

Product Grade

L1211FA

Recycling

- The product is suitable for recycling using modern methods of shredding and cleaning. In-house production waste should be kept clean to facilitate direct recycling.
- Please see our Safety Data Sheet for details on various aspects of safety, recovery, and disposal of the products; for more information, contact your Long Son Petrochemicals technical services or SCG Chemicals technical services.

Related Documents

- The latest version of this document will be available at our website, www.lsp.com or www.scgchemicals, or can be obtained from the Long Son Petrochemicals technical services or SCG Chemicals technical services.
- The following related documents are available on request, and represent various aspects on the usability, safety, recovery, and disposal of the product.
 - Safety Data Sheet
 - Declaration of compliance.

Disclaimer

- The Applications specified herein is for reference only.
- It is customer's responsibilities to inspect and test the product for suitability of the customer's own use and purpose. The customer is responsible for appropriate, safe, legal use, processing, and handling of the product.
- To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication. We however do not assume any liability whatsoever for the accuracy and completeness of the information contained herein.
- We make no warranties which extend beyond the description herein. Nothing herein shall constitute any implied warranty of merchantability or fitness for a particular purpose.
- No liability can be accepted in respect of the use of the product in conjunction with other materials. The information contained herein relates exclusively to the product when it is not used in conjunction with any third party's materials.